Owner's Handbook supplement

CABRIO

HOLDEN

LOWERING THE ROOF

From the driver's seat release the two securing levers situated above the windscreen.



Lift the front section of the roof and release the two small strap clips.



Lift the front cover off the roof frame and then re-secure the front frame (from inside the car) by pushing it down and locking it with the front securing levers.





Lay the cover flat over the front of the roof.



LOWERING THE ROOF cont.

* Move to one side of the car and release the side window frame by firmly depressing the handle inside the car (next to the rear side window).



* Undo the stud at the rear of the side window and unzip fully.





* From outside the car lift the frame up and remove the side window flap from the frame. Then lay the window flap on the rooftop.





Repeat the above three steps (marked with the *) with the other side window.

LOWERING THE ROOF cont.

Both side window flaps should be laying flat on the rooftop, slightly overlapping at the centre.



Fold the front of the roof in half over the rear roof section and then fold it in half again.



Move to the back of the car and slowly bring the folded roof towards you, while folding the rear window. It is important to ensure that the rear window has one horizontal crease, as shown, but does not crease vertically. When the roof is fully down push forward slightly.





The tonneau is usually stored behind the rear seats. Move the rear seat forward (push the buttons on top of the seat), pull up the tonneau and move the seat back to the upright position.



Secure the tonneau fastening clips, then studs and finally secure the cover side straps under the side window frames, and re-secure the side window frame by pressing firmly home.



RAISING THE ROOF

Release the tonneau straps, studs and clips and stow behind the rear seat.



Lift the roof over the top of the car.



To secure the side windows:

Fit the window flap around the side window frame, zip up the side and fasten the stud. Secure the window frame by pressing firmly at the front, lower corner.



Repeat the above steps with the other side window.



From the side of the car (you may need to stand on the door sill) replace the front roof cover over the front roof frame, ensuring the small straps fall behind the frame.



RAISING THE ROOF cont.

Fasten the small straps to the front of the roof frame bar.



From inside the car, close the front of the roof with the two securing levers.



Note that the roof can also be partially opened:
Release the two front securing levers, grasp the centre bar and lift the roof upwards and backwards. Fold the roof as far as the back of the driver's seat.

CLEANING YOUR CABRIO

To avoid damage to the roof, your Cabrio should not be washed at a automatic car wash, but instead washed by hand. Refer chapter 11 of the Owner's Handbook.

ANTENNA

The antenna on your car is fitted near the base of the windscreen, on the left hand side.
To guard against breakage, the antenna can be pushed fully down. To extend the antenna again, insert the antenna key in the antenna slots and pull the antenna up.
The best radio reception is gained when the antenna is fully extended.